


PIN NO.	SYMBOL
1	DB0
2	DB1
3	DB2
4	DB3
5	GND1
6	VCI 2.8
7	/CS
8	RS
9	/WR
10	/RD
11	IM0(nc)
12	X+
13	Y+
14	X-
15	Y-
16	LED-A
17	LED-1
18	LED-2
19	LED-3
20	LED-4
21	NC
22	DB4
23	DB8
24	DB9
25	DB10
26	DB11
27	DB12
28	DB13
29	DB14
30	DB15
31	/RESET
32	VCI 2.8
33	1OVCC
34	GND
35	DB5
36	DB6
37	DB7
38	nc
39	nc
40	nc


PI+FPC=0.3±0.05



NOTES:

1. DISPLAY TYPE: TFT
2. VIEWING DIRECTION: ALL
3. LCD DRIVE IC: ILI9341
4. POLARIZER MODE: TRANSMISSIVE/POSITIVE
5. VDD : 2.5V-3.3V, IOVDD : 1.65V-3.3V
6. BACKLIGHT: 4-CHIP WHITE LED PARALLEL
7. OPERATING TEMP: -20° C~+70° C
8. STORAGE TEMP: -30° C~+80° C
9. UNMARKER TOLERANCE: ±0.20

深圳市艾斯迪科技有限公司



PRJ(3)

UNIT: MM	SIZE: A4	Scale: 1/1	GENERAL TOLERANCE: ±0.2 Angle=1°	
DESIGNED:		DATE: 2019-10-12	PROJECT NO.	SHEET:1/1
CHECKED:		DATE:	PART NO.	REV: A
APPROVED:		DATE:		